

## Instructions

Make sure all locks and clips are secured before and during use. Do not leave tripods unattended on uneven surfaces, in high winds or in public places where others might injure themselves. Whenever possible remove equipment from the support during transportation.

## Care & Cleaning

Always dry the equipment thoroughly after use in damp or wet conditions. Avoid contact with salt water. To clean the equipment, remove excess dirt and dust from moving parts (threads and sliding sections) using compressed air or a blower brush. Wash with a mild detergent and dry thoroughly with a soft cloth. Whenever possible store in a stable dry atmosphere away from moisture. Do not attempt to dismantle the equipment as this will invalidate the guarantee.

## Guarantee

Opticron tripods\* listed herein are guaranteed for up to 5 years under the following conditions.

- (i) In the case of faults attributable to faulty processing or materials, we will assume responsibility for the labour and material costs during the first 2 years after purchase. We reserve the right to decide whether defective parts should be repaired or replaced.
- (ii) During the next 3 years we will assume responsibility for material costs only, charging corresponding labour costs.
- (iii) We will accept no liability for damage caused by incorrect use, water damage or for any repairs or actions carried out outside our firm.

Items such as carry straps and rubberised coatings are excluded from the guarantee.

This guarantee is in addition to and does not affect your statutory rights.

\*Manfrotto and Velbon panheads are covered by their own manufacturer's guarantees.

**opticron**



**opticron**

**Address:** Opticron, Unit 21, Titan Court, Laporte Way,  
Luton, Bedfordshire, LU4 8EF, UK

**Phone:** +44 (0)1582 726522 **Fax:** +44 (0)1582 723559


**Email:** sales@opticron.co.uk

**XFS-C Tripods & Optional Panheads**

User Guide & Guarantee

## 42116 XFS-C Traveller 4-section Tripod

- 8 layer carbon fibre with twist lock
- Leg angles; 25°, 55°, 80°
- Foam hand grips & rubber/spiked feet
- Level indicator
- 24mm dia, 330mm removable centre column with sprung stabilising hook
- Max. height: 1500mm
- Max. height w/o raising c/c: 1250mm
- Min. height (25°): 455mm
- Length (storage): 480mm
- Weight: 1050g
- 5 year guarantee



## 42122 XFS-C Birdwatcher's 3-section Tripod

- 8 layer carbon fibre with twist lock
- Leg angles; 25°, 55°, 80°
- Foam hand grips & rubber/spiked feet
- Level indicator
- 24mm dia, 330mm removable centre column with sprung stabilising hook
- Max height: 1555mm
- Max. height w/o raising c/c: 1305mm
- Min. height (25°): 560mm
- Length (storage): 595mm
- Weight: 1170g
- 5 year guarantee



## 20897 Velbon PH157QK Panhead

- 3-way one lever operated with 360° pan, +90°/-60° tilt
- 90° side tilt
- QR plate (1/4")
- 1/4" connection to c/column
- Height: 100mm
- Weight: 577g
- Manufacturers max. load rating: 3.5kg
- 5 year manufacturer's guarantee



## 35857 Manfrotto 700RC2 Panhead

- 2-way with 360° pan, +90°/-75° tilt
- Tension control
- Adjustable pan handle
- QR plate (1/4")
- 3/8" connection to c/column
- Height: 100mm
- Weight: 520g
- Manufacturers max. load rating: 2.5kg
- 5 year manufacturer's guarantee

